

**2 & 3-4 Rooms Multi**

**Wall mounted**



Model No.	Indoor unit		ASAG07LMCA	ASAG09LMCA	ASAG12LMCA	ASYG07LUCA	ASYG09LUCA	ASYG12LUCA	
kW Class			kW	2.0	2.5	3.5	2.0	2.5	3.5
Power Source			V/Ø/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Air Flow	Cooling	H/M/L/Q	m³/h	560/500/430/310	600/520/430/310	660/560/450/310	570/520/470/330	600/550/470/330	660/600/530/330
	Heating	H/M/L/Q	m³/h	560/500/430/330	600/520/430/330	660/560/470/330	570/520/470/330	600/550/470/330	660/600/530/330
Sound pressure level	Cooling	H/M/L/Q	dB(A)	36/32/29/21	37/33/29/21	40/36/30/21	35/30/28/21	36/32/28/21	37/34/31/21
	Heating	H/M/L/Q	dB(A)	36/32/29/22	37/33/29/22	40/36/31/22	35/30/28/21	36/32/28/21	37/34/31/21
Net Dimension H × W × D			mm	268x840x203	268x840x203	268x840x203	282x870x185	282x870x185	282x870x185
Weight			kg (lbs)	8.5(18.7)	8.5(18.7)	8.5(18.7)	9.5(20.9)	9.5(20.9)	9.5(20.9)
Piping Connections	Liquid/Gas		mm	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø9.52

**Wall mounted**




Model No.	Indoor unit		ASAG18LFCA	ASAG24LFCA	
kW Class			kW	5.0	7.0
Power Source			V/Ø/Hz	230/1/50	230/1/50
Air Flow	Cooling	H/M/L/Q	m³/h	900/740/620/550	1120/900/740/620
	Heating	H/M/L/Q	m³/h	900/740/620/550	1100/900/740/620
Sound pressure level	Cooling	H/M/L/Q	dB(A)	43/37/33/26	49/42/37/33
	Heating	H/M/L/Q	dB(A)	42/37/33/25	48/42/37/33
Net Dimension H × W × D			mm	320x998x238	320x998x238
Weight			kg (lbs)	14(30.9)	14(30.9)
Piping Connections	Liquid/Gas		mm	Ø6.35/Ø12.70	Ø6.35/Ø15.88

**Compact cassette**



Model No.	Indoor unit		AUAG09LVLA	AUAG12LVLA	AUAG14LVLA	AUAG18LVLA	
kW Class			kW	2.5	3.5	4.0	5.0
Power Source			V/Ø/Hz	230/1/50	230/1/50	230/1/50	230/1/50
Air Flow	Cooling	H/M/L/Q	m³/h	540/490/440/390	610/530/470/410	680/580/490/410	750/610/520/410
	Heating	H/M/L/Q	m³/h	540/490/440/390	610/530/470/410	700/620/550/430	800/710/600/450
Sound pressure level	Cooling	H/M/L/Q	dB(A)	33/31/29/27	37/33/31/28	40/35/32/29	42/37/33/29
	Heating	H/M/L/Q	dB(A)	34/32/29/27	37/33/31/28	40/37/34/29	44/40/37/30
Net Dimension H × W × D			mm	245x570x570	245x570x570	245x570x570	245x570x570
Weight			kg (lbs)	15(33.1)	15(33.1)	15(33.1)	15(33.1)
Panel			UTG-UFYD-W				
Piping Connections	Liquid/Gas		mm	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø12.70	Ø6.35/Ø12.70

**Slim duct**



Model No.	Indoor unit		ARAG09LLLA	ARAG12LLLA	ARAG14LLLA	ARAG18LLLA	ARAG24LLLA	
kW Class			kW	2.5	3.5	4.0	5.0	7.0
Power Source			V/Ø/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Air Flow	Cooling	H/M/L/Q	m³/h	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750	1330/1240/1100/1030
	Heating	H/M/L/Q	m³/h	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750	1330/1240/1100/1030
Sound pressure level	Cooling	H/M/L/Q	dB(A)	28/27/26/25	29/28/27/26	32/30/28/26	32/31/30/29	33/32/30/29
	Heating	H/M/L/Q	dB(A)	28/26/25/24	29/28/27/24	33/30/28/25	33/32/31/29	35/34/32/29
Net Dimension H × W × D			mm	198x700x620	198x700x620	198x700x620	198x900x620	198x1100x620
Weight			kg (lbs)	19(41.9)	19(41.9)	19(41.9)	23(50.7)	27(59.5)
Piping Connections	Liquid/Gas		mm	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø12.70	Ø6.35/Ø12.70	Ø6.35/Ø15.88
External static pressure			0 to 90				0 to 50	
Drain pump			Standard					

## 5-6 Rooms Multi

### Wall mounted

Model No.	Indoor unit		ASYG07LUCA	ASYG09LUCA	ASYG12LUCA	ASYG14LUCA
kW Class	kW		2.0	2.5	3.5	4.0
Power Source	V/Hz		230/1/50	230/1/50	230/1/50	230/1/50
Sound Pressure Level	Cooling	H/M/L/Q	35/30/28/21	36/32/28/21	37/34/31/21	41/36/33/25
	Heating		35/30/28/21	36/32/28/21	37/34/31/21	41/36/34/27
Airflow rate	Cooling	H/M/L/Q	570/520/470/330	600/550/470/330	660/600/530/330	710/640/570/390
	Heating		570/520/470/330	600/550/470/330	660/600/530/330	710/640/590/430
Net Dimension H×W×D	mm		282x870x185	282x870x185	282x870x185	282x870x185
Weight	kg (lbs)		9.5 (21)	9.5 (21)	9.5 (21)	9.5 (21)
Piping connections	Liquid/Gas	mm	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø12.70

### Wall mounted

Model No.	Indoor unit		ASYG07LMCA	ASYG09LMCA	ASYG12LMCA	ASYG14LMCA	ASYG18LFCA	ASYG24LFCA	ASYG24LFCC
kW Class	kW		2.0	2.5	3.5	4.0	5.0	7.0	7.0
Power Source	V/Hz		230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Sound Pressure Level	Cooling	H/M/L/Q	36/32/29/21	37/33/29/21	40/36/30/21	42/38/33/25	43/37/33/26	49/42/37/33	49/42/37/33
	Heating		36/32/29/22	37/33/29/22	40/36/31/22	42/38/35/27	42/37/33/25	48/42/37/33	48/42/37/33
Airflow rate	Cooling	H/M/L/Q	560/500/430/310	600/520/430/310	660/560/450/310	730/600/530/360	900/740/620/550	1,120/900/740/620	1,120/900/740/620
	Heating		560/500/430/330	600/520/430/330	660/560/470/330	730/615/560/375	900/740/620/550	1,100/900/740/620	1,100/900/740/620
Net Dimension H×W×D	mm		268x840x203	268x840x203	268x840x203	268x840x203	320x998x238	320x998x238	320x998x238
Weight	kg (lbs)		8.5 (19)	8.5 (19)	8.5 (19)	8.5 (19)	14 (30.8)	14 (30.8)	14 (30.8)
Piping connections	Liquid/Gas	mm	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø12.70	Ø6.35/Ø12.70	Ø6.35/Ø15.88	Ø6.35/Ø15.88

### Floor / Floor ceiling

Model No.	Indoor unit		AGYG09LVCA	AGYG12LVCA	AGYG14LVCA	ABYG14LVTA	ABYG18LVTB
kW Class	kW		2.5	3.5	4.0	4.0	5.0
Power Source	V/Hz		230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Sound Pressure Level	Cooling	H/M/L/Q	39/34/28/22	42/36/30/22	44/38/31/22	36/34/33/29 (Under ceiling) 39/37/36/32 (Floor console)	41/38/34/32 (Under ceiling) 44/41/37/35 (Floor console)
	Heating		39/35/30/22	42/38/32/22	44/39/33/22	36/34/33/29 (Under ceiling) 39/37/36/32 (Floor console)	41/38/34/32 (Under ceiling) 44/41/37/35 (Floor console)
Airflow rate	Cooling	H/M/L/Q	530/440/360/270	600/490/380/270	650/520/400/270	640/590/540/480	780/700/560/500
	Heating		530/460/380/270	600/510/410/270	650/540/430/270	640/590/540/480	780/700/560/500
Net Dimension H×W×D	mm		600x740x200	600x740x200	600x740x200	199x990x655	199x990x655
Weight	kg (lbs)		14 (30.7)	14 (30.7)	14 (30.7)	27 (60)	27 (60)
Piping connections	Liquid/Gas	mm	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø12.70	Ø6.35/Ø12.70	Ø6.35/Ø12.70

### Compact cassette

Model No.	Indoor unit		AUYG07LVLA	AUYG09LVLA	AUYG12LVLB	AUYG14LVLB	AUYG18LVLB
kW Class	kW		2.0	2.5	3.5	4.0	5.0
Power Source	V/Hz		230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Sound Pressure Level	Cooling	H/M/L/Q	33/31/29/27	33/31/29/27	37/33/31/28	40/35/32/29	42/37/33/29
	Heating		34/32/29/27	34/32/29/27	37/33/31/28	40/37/34/29	44/40/37/30
Airflow rate	Cooling	H/M/L/Q	540/490/440/390	540/490/440/390	610/530/470/410	680/580/490/410	750/610/520/410
	Heating		540/490/440/390	540/490/440/390	610/530/470/410	700/620/550/430	800/710/600/450
Net Dimension H×W×D	mm		245x570x570	245x570x570	245x570x570	245x570x570	245x570x570
Weight	kg (lbs)		15 (33.1)	15 (33.1)	15 (33.1)	15 (33.1)	15 (33.1)
Cassette Grille			UTG-UFYD-W				
Piping connections	Liquid/Gas	mm	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø12.70	Ø6.35/Ø12.70

### Slim duct

Model No.	Indoor unit		ARYG07LLTA	ARYG09LLTA	ARYG12LLTB	ARYG14LLTB	ARYG18LLTB
kW Class	kW		2.0	2.5	3.5	4.0	5.0
Power Source	V/Hz		230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Sound Pressure Level	Cooling	H/M/L/Q	28/26/25/24	28/27/26/25	29/28/27/26	32/30/28/26	32/31/30/29
	Heating		28/26/25/24	28/26/25/24	29/28/27/24	33/30/28/25	33/32/31/29
Airflow rate	Cooling	H/M/L/Q	550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750
	Heating		550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750
Net Dimension H×W×D	mm		198x700x620	198x700x620	198x700x620	198x700x620	198x900x620
Weight	kg (lbs)		17 (37.5)	19 (41.8)	19 (41.8)	19 (41.8)	23 (50.6)
Piping connections	Liquid/Gas	mm	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø12.70	Ø6.35/Ø12.70
External static pressure			0 to 90				
Drain pump			Standard				

### Mini duct

Model No.	Indoor unit		ARYG07LSLAP	ARYG09LSLAP	ARYG12LSLAP	ARYG14LSLAP	ARYG18LSLAP
kW Class	kW		2.0	2.5	3.5	4.0	5.0
Power Source	V/Hz		230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Sound Pressure Level	Cooling	H/M/L/Q	29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23	33/29/26/23
	Heating		29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23	33/29/26/23
Airflow rate	Cooling	H/M/L/Q	550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360	940/750/540/480
	Heating		550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360	940/750/540/480
Net Dimension H×W×D	mm		198x700x450	198x700x450	198x700x450	198x700x450	198x900x450
Weight	kg (lbs)		15.5 (34.1)	15.5 (34.1)	15.5 (34.1)	15.5 (34.1)	18.5 (40.7)
Piping connections	Liquid/Gas	mm	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø9.52	Ø6.35/Ø12.70	Ø6.35/Ø12.70
External static pressure			0 to 30				
Drain pump			Standard				0 to 50